

Engine

Model	Yanmar 4TNV94L
Туре	Direct Injection (DI), Water Cooled
No. of Cylinders	4-Cylinder Diesel Engine
Net Peak Power	43kW (57.6HP) @ 3000 rpm
Fuel Tank Capacity	105 Litres

■Hydraulic System

Circuit Type	Axial Piston, Gear Pump	
Pump Capacity	L/min	2x59.2+42.2
System Pressure	MPa	20
Tank Capacity	L	120
Traveling & San Traveling & Sa	- I Doos	an Parker & Fat

Overall Dimensions


Overall Length	mm	5850
Overall Width	mm	1885
Overall Height	mm	2575
Ground Clearance	mm	350
Track Length	mm	2540
Track Width	mm	400
Boom Length	mm	1600
Platform Ground Clearance	mm	830

Operation Parameters

Operation Weight	kg	5580
Standard Bucket Capacity	m³	0.2
Max. Digging Depth	mm	3820
Max. Vertical Digging Depth	mm	2900
Max. Ground Level Digging Reach	mm	6100
Max. Digging Distance	mm	6150
Max. Working Height	mm	5760
Max. Dumping Height	mm	4030
Tail Swing Radius	mm	1800

Under our policy of continuous improvement, we reserve the right to change technical data and design without prior notice.





■Main Performance

Swing Speed	rpm T	12
Traveling Speed	km/h	2.5/4
Grade Ability	Degrees	35
Ground Pressure	KPa	34
Drawbar Bullian Fares		50.4

Drawbar Pulling Force	kN	50.4
Bucket Digging Force	kN	37.7
Arm Digging Force	kN	28.4

ATTACHMENTS &

