



## ■ Technical Specifications

ENGINE	
Model	Changchai 3LS30B
Type	Direct injection, water-cooled
Engine Peak Power @ 2400rpm	22.1kW (30HP)
PTO Peak Power	19.9kW (27HP)
Cylinders	3 Cylinder Diesel Engine
Displacement	1.813
Fuel Tank Capacity	28L
DRIVE TRAIN	
Transmission	Synchro Shuttle 8F/8R
Min/Max Forward Speed (km/h)	1.44 - 26.10
Steering	Power
Clutch	Dry, Dual-Stage
Brake	Dry, Disk
Differential Lock	Mechanical
Drive Type	4WD
PTO	
Rear PTO (rpm)	Live 540/1,000
Spline Size	6-ø35 Rectangular Spline
HYDRAULICS	
Pump Type	Gear (Tandem)
Implement Pump	24 L/min
3-Point Hitch	CAT.1
Lift Capacity	496kg

\*Under our policy of continuous improvement, we reserve the right to change technical data and design without prior notice.

DIMENSIONS	
Overall Length	3380mm
Overall Width	1550mm
Overall Height	1511mm
Wheelbase	1732mm
Min. Ground Clearance	296mm
Min. Turning Radius	3200mm
Weight	1350kg
TIRES	
Agriculture	6.00-12/11.2-20
Industrial	23X8.5-12/14-17.5



## BUILDING THE FUTURE