



## ■ Technical Specifications

ENGINE	
	Changchai 4LD40B
Type	Direct injection, water-cooled
Engine Peak Power @ 2400rpm	29.4kW (40HP)
PTO Peak Power	26.5kW (36HP)
Cylinders	4 Cylinder Diesel Engine
Displacement	2.543
Fuel Tank Capacity	28L
DRIVE TRAIN	
Transmission	Synchro Shuttle 8F/8R
Min/Max Forward Speed (km/h)	1.48 - 26.86
Steering	Power
Clutch	Dry, Dual-Stage
Brake	Dry, Disk
Differential Lock	Mechanical
Drive Type	4WD
PTO	
Rear PTO (rpm)	Live 540/1,000
Spline Size	6-ø35 Rectangular Spline
HYDRAULICS	
Pump Type	Gear (Tandem)
Implement Pump	24 L/min
3-Point Hitch	CAT.1
Lift Capacity	665kg

\*Under our policy of continuous improvement, we reserve the right to change technical data and design without prior notice.

DIMENSIONS	
Overall Length	3515mm
Overall Width	1630mm
Overall Height	1600mm
Wheelbase	1900mm
Min. Ground Clearance	381mm
Min. Turning Radius	3800mm
Weight	1525kg
TIRES	
Agriculture	7.5-16/12.4-24
Industrial	10-16.5/16.5-22.5



## BUILDING THE FUTURE