



# MCM

 <b>RATED LOAD</b> <b>1500</b> kg	 <b>ENGINE POWER</b> <b>60</b> hp
 <b>SPEED</b> <b>24</b> km/h	 <b>FLOW RATE</b> <b>96</b> l/min
	 <b>LIFT HEIGHT</b> <b>3.51</b> m

## Technical Specifications

Model	ML50
<b>Engine</b>	YUNNEI ENGINE
<b>Power</b>	60hp/44.7kw
<b>Fuel</b>	Diesel
<b>Transmission</b>	4WD Hydrostatic
<b>Drive Speed</b>	0-12-24km/h
<b>Working Hydraulic Flow</b>	48L/min*2
<b>*Max. Lift Height (Extended)</b>	3.515m
<b>*Max. Lift Height (Retracted)</b>	2.886m
<b>Lifting Capacity</b>	1500kg
<b>Min. Turning Radius</b>	3200mm
<b>Max. Turning Angle</b>	45 degrees
<b>Operating Weight</b>	2400kg
<b>Fuel Tank Capacity</b>	42L
<b>Battery Capacity</b>	60 Ah
<b>Standard Tires</b>	31x15.5-15
<b>Overall Dimensions (L*W*H)</b>	3694x1560x2378

## Standard Features

- 4WD Direct Drive Hydrostatic Motors
- DBS (Dynamic Block System)
- Self-levelling Telescopic Boom
- Hydraulic Multiconnector/Quick Hitch
- Boom Floating Function
- Multifunctional Hydraulic Joystick
- ROPS-FOPS Closed Cabin
- Removable Cabin Doors
- Adjustable Steering Column
- Air Suspension Seat
- Standard Bucket
- Central Articulation(Vertical/Horizontal)

Engine Options

**YANMAR**  
**KOHLER**<sup>®</sup>

## Optional Attachments

There are over 60 attachments to choose from; each with its own unique application.

\*Lifting heights were measured while equipped with standard bucket.

\*\*Terms and Conditions apply. Under our policy of continuous improvement, MCM reserves the right to change technical data and design without prior notice.