

MCM

RTL30Q



Technical Specifications

Parameters

Machine	RTL30Q
Engine	Yunnei 490
Rated Power / r.p.m	42 kW
Rated Torque / r.p.m	202 Nm
No. of Cylinders	4
Fuel Tank Capacity	60L
Transmission	Automatic
Load Capacity	3000kg
Load Center	500mm
Wheels (x=driven)	4

Dimensions

Max. Lifting Height (STND.)	4500mm
Free Lift	128mm
Fork Size	1070 x 122 x 45mm
Fork Spread	1280mm
Tilt Angle	6° / 6°
Lenght to Fork Face	3800mm
Overall Width	180mm
Mast Height Fork Lowered	2275mm
Mast Height Fork Raised	5600mm
Overhead Guard Height	2170mm
Operator's Seat Height	1000mm
Min. Turning Radius	4050mm
Load Distance	1070mm
Rear Overhang	610mm

Other

Under our policy of continuous improvement, we reserve the right to change technical data and design without prior notice.

Performance

Speeds	Max. Travel	17km/h
	Lifting	530/550mm/sec
	Lowering	450/550mm/sec
Max. Drawbar Pull	Full Load	2000kN
	No Load	1500kN
Max. Gradeability	Full Load	20%
	No Load	22%
Operating Weight		4680kg
Tyres Size	Front	7.00-12-12PR
	Rear	6.00-9-10PR
Wheelbase		1600mm
Tread	Front	970mm
	Rear	970mm
Overhead Guard Clearance		115mm
Counterweight Height		140mm
Underclearance		170mm
Brake		Hydraulic
Battery		12/80 V/AH

Diagram

